

### Input DLIS Files

DEFAULT      HAIT .048      FN:70 PRODUCER      27-Dec-1999 11:59      10866.0 FT      9461.0 FT

### Output DLIS Files

DEFAULT      HAIT .053      FN:81 PRODUCER      27-Dec-1999 12:54  
 BACKUP      HAIT .053      FN:82 PRODUCER      27-Dec-1999 12:53  
 REDUCED      HAIT .053      FN:83 PRODUCER      27-Dec-1999 12:54

177204014901

## RUN 1

### Directional Survey Manually-Entered Inclination Summary

Tie In Point : Measured Depth True Vertical Depth

1122.00 FT

1121.82 FT

Depth	Deviation	True Vertical Depth	Depth	Deviation	True Vertical Depth
1122.00 FT	0.75 DEG	1121.82 FT	5590.00 FT	47.46 DEG	5259.44 FT
1312.00 FT	0.80 DEG	1311.80 FT	5686.00 FT	48.63 DEG	5323.62 FT
1407.00 FT	0.74 DEG	1406.79 FT	5780.00 FT	51.30 DEG	5384.08 FT
1502.00 FT	0.78 DEG	1501.79 FT	5875.00 FT	50.55 DEG	5443.96 FT
1596.00 FT	0.96 DEG	1595.77 FT	5970.00 FT	49.99 DEG	5504.68 FT
1691.00 FT	0.96 DEG	1690.76 FT	6065.00 FT	49.32 DEG	5566.19 FT
1786.00 FT	1.00 DEG	1785.75 FT	6159.00 FT	50.27 DEG	5626.86 FT
1881.00 FT	1.00 DEG	1880.73 FT	6254.00 FT	49.44 DEG	5686.11 FT
1975.00 FT	1.06 DEG	1974.72 FT	6349.00 FT	51.14 DEG	5746.80 FT
2070.00 FT	1.40 DEG	2069.69 FT	6444.00 FT	50.54 DEG	5806.80 FT
2165.00 FT	1.52 DEG	2164.86 FT	6538.00 FT	50.17 DEG	5866.77 FT
2261.00 FT	1.75 DEG	2260.62 FT	6633.00 FT	49.70 DEG	5929.92 FT
2356.00 FT	1.92 DEG	2355.58 FT	6728.00 FT	49.15 DEG	5991.71 FT
2452.00 FT	2.28 DEG	2451.51 FT	6822.00 FT	50.74 DEG	6052.20 FT
2547.00 FT	2.61 DEG	2546.42 FT	6917.00 FT	50.63 DEG	6112.39 FT
2642.00 FT	3.47 DEG	2641.29 FT	7012.00 FT	50.22 DEG	6172.91 FT
2737.00 FT	3.78 DEG	2736.10 FT	7107.00 FT	49.85 DEG	6233.93 FT
2832.00 FT	4.01 DEG	2830.88 FT	7202.00 FT	49.28 DEG	6295.55 FT
2928.00 FT	4.07 DEG	2926.64 FT	7297.00 FT	48.61 DEG	6357.94 FT
3023.00 FT	3.96 DEG	3021.41 FT	7393.00 FT	49.36 DEG	6420.93 FT
3118.00 FT	5.76 DEG	3116.06 FT	7488.00 FT	48.96 DEG	6483.04 FT
3214.00 FT	7.73 DEG	3211.39 FT	7583.00 FT	48.15 DEG	6545.92 FT
3308.00 FT	9.62 DEG	3304.31 FT	7678.00 FT	48.59 DEG	6609.03 FT
3403.00 FT	11.36 DEG	3397.72 FT	7773.00 FT	49.31 DEG	6671.42 FT



ds0057432

3492.00 FT	13.52 DEG	3484.63 FT	7868.00 FT	49.04 DEG	6733.53 FT
3593.00 FT	14.98 DEG	3582.52 FT	7963.00 FT	48.54 DEG	6796.12 FT
3688.00 FT	16.07 DEG	3674.05 FT	8059.00 FT	49.15 DEG	6859.29 FT
3783.00 FT	17.63 DEG	3764.97 FT	8154.00 FT	48.57 DEG	6921.79 FT
3878.00 FT	19.49 DEG	3855.02 FT	8249.00 FT	49.17 DEG	6984.28 FT
3973.00 FT	21.98 DEG	3943.86 FT	8333.70 FT	48.60 DEG	7039.98 FT
4068.00 FT	24.53 DEG	4031.14 FT	8345.00 FT	48.53 DEG	7047.45 FT
4162.00 FT	27.28 DEG	4115.68 FT	8427.00 FT	48.95 DEG	7102.60 FT
4235.00 FT	29.09 DEG	4180.02 FT	8485.00 FT	48.60 DEG	7142.32 FT
4354.00 FT	29.43 DEG	4283.84 FT	8581.00 FT	45.58 DEG	7208.90 FT
4449.00 FT	29.26 DEG	4366.65 FT	8676.00 FT	45.22 DEG	7275.60 FT
4544.00 FT	29.77 DEG	4449.32 FT	8771.00 FT	45.45 DEG	7342.38 FT
4639.00 FT	31.33 DEG	4531.13 FT	8867.00 FT	46.09 DEG	7409.35 FT
4735.00 FT	33.44 DEG	4612.20 FT	8962.00 FT	46.56 DEG	7474.95 FT
4830.00 FT	35.44 DEG	4690.54 FT	9057.00 FT	46.72 DEG	7540.18 FT
4925.00 FT	37.97 DEG	4766.70 FT	9151.00 FT	47.15 DEG	7604.36 FT
5020.00 FT	40.15 DEG	4840.46 FT	9246.00 FT	47.59 DEG	7668.70 FT
5115.00 FT	40.87 DEG	4912.89 FT	9341.00 FT	47.11 DEG	7733.06 FT
5210.00 FT	40.56 DEG	4984.89 FT	9436.00 FT	46.53 DEG	7798.07 FT
5305.00 FT	41.86 DEG	5056.18 FT	9532.00 FT	46.81 DEG	7863.95 FT
5400.00 FT	43.17 DEG	5126.18 FT	9626.00 FT	46.74 DEG	7928.32 FT
5495.00 FT	45.59 DEG	5194.08 FT	9714.00 FT	46.53 DEG	7988.75 FT
5578.04 FT	47.18 DEG	5249.98 FT	9790.00 FT	46.53 DEG	8041.04 FT

## RUN 2 Directional Survey Manually-Entered Inclineretry Summary

Tie In Point : Measured Depth True Vertical Depth North Departure East Departure

7297.00 FT

6357.97 FT

2340.92 FT

-799.50 FT

Depth	Deviation	Azimuth	True Vertical Depth	North Departure	East Departure
7297.00 FT	48.61 DEG	336.76 DEG	6357.97 FT	2340.92 FT	-799.50 FT
7393.00 FT	49.38 DEG	336.31 DEG	6420.96 FT	2407.38 FT	-828.35 FT
7488.00 FT	48.96 DEG	336.63 DEG	6483.07 FT	2473.28 FT	-857.05 FT
7583.00 FT	48.15 DEG	336.71 DEG	6545.95 FT	2538.67 FT	-885.25 FT
7678.00 FT	48.59 DEG	336.62 DEG	6609.06 FT	2603.67 FT	-913.38 FT
7773.00 FT	49.31 DEG	336.68 DEG	6671.45 FT	2669.65 FT	-941.78 FT
7868.00 FT	49.04 DEG	336.44 DEG	6733.55 FT	2735.58 FT	-970.38 FT
7963.00 FT	48.54 DEG	336.67 DEG	6796.14 FT	2801.15 FT	-998.81 FT
8059.00 FT	49.15 DEG	337.31 DEG	6859.32 FT	2867.71 FT	-1027.06 FT

8154.00 FT	48.57 DEG	337.64 DEG	6921.82 FT	2933.79 FT	-1054.46 FT
8249.00 FT	49.17 DEG	338.76 DEG	6984.31 FT	3000.23 FT	-1081.03 FT
8333.70 FT	48.60 DEG	338.93 DEG	7040.00 FT	3059.74 FT	-1104.06 FT
8345.00 FT	48.53 DEG	339.11 DEG	7047.48 FT	3067.65 FT	-1107.09 FT
8427.00 FT	46.95 DEG	336.96 DEG	7102.62 FT	3123.93 FT	-1129.79 FT
8485.00 FT	46.60 DEG	337.02 DEG	7142.35 FT	3162.83 FT	-1146.31 FT
8581.00 FT	45.58 DEG	336.28 DEG	7208.92 FT	3226.33 FT	-1173.72 FT
8676.00 FT	45.22 DEG	334.71 DEG	7275.63 FT	3287.68 FT	-1201.77 FT
8771.00 FT	45.45 DEG	334.07 DEG	7342.41 FT	3348.81 FT	-1230.97 FT
8867.00 FT	46.09 DEG	336.71 DEG	7409.37 FT	3411.34 FT	-1259.61 FT
8962.00 FT	46.56 DEG	336.63 DEG	7474.98 FT	3474.43 FT	-1286.83 FT
9057.00 FT	46.72 DEG	338.32 DEG	7540.20 FT	3538.23 FT	-1313.28 FT
9151.00 FT	47.15 DEG	338.92 DEG	7604.39 FT	3602.18 FT	-1338.32 FT
9246.00 FT	47.59 DEG	340.23 DEG	7668.73 FT	3667.68 FT	-1362.71 FT
9341.00 FT	47.11 DEG	339.87 DEG	7733.09 FT	3733.37 FT	-1386.55 FT
9436.00 FT	46.53 DEG	339.65 DEG	7798.10 FT	3798.36 FT	-1410.51 FT
9532.00 FT	46.81 DEG	339.70 DEG	7863.98 FT	3863.84 FT	-1434.77 FT
9626.00 FT	46.74 DEG	339.75 DEG	7928.35 FT	3928.11 FT	-1458.52 FT
9714.00 FT	46.53 DEG	339.84 DEG	7988.78 FT	3988.15 FT	-1480.61 FT
9830.00 FT	46.17 DEG	341.15 DEG	8068.84 FT	4067.26 FT	-1508.64 FT
9925.00 FT	47.13 DEG	338.42 DEG	8134.06 FT	4132.08 FT	-1532.51 FT
10021.00 FT	47.92 DEG	338.16 DEG	8198.88 FT	4197.86 FT	-1558.71 FT
10116.00 FT	48.36 DEG	337.63 DEG	8262.28 FT	4263.42 FT	-1585.35 FT
10211.00 FT	47.92 DEG	339.74 DEG	8325.67 FT	4329.33 FT	-1611.06 FT
10306.00 FT	46.96 DEG	340.27 DEG	8389.93 FT	4395.06 FT	-1634.99 FT
10401.00 FT	47.04 DEG	339.74 DEG	8454.71 FT	4460.38 FT	-1658.75 FT
10497.00 FT	47.40 DEG	340.30 DEG	8519.92 FT	4526.60 FT	-1682.82 FT
10592.00 FT	45.60 DEG	339.20 DEG	8585.31 FT	4591.25 FT	-1706.67 FT
10686.00 FT	46.25 DEG	338.16 DEG	8650.69 FT	4654.15 FT	-1731.22 FT
10782.00 FT	46.80 DEG	338.20 DEG	8716.75 FT	4718.63 FT	-1757.11 FT
10877.00 FT	47.40 DEG	339.10 DEG	8781.41 FT	4783.64 FT	-1782.45 FT
10973.00 FT	47.48 DEG	339.39 DEG	8846.35 FT	4849.76 FT	-1807.51 FT
11069.00 FT	47.92 DEG	339.39 DEG	8910.96 FT	4916.22 FT	-1832.50 FT
11164.00 FT	47.13 DEG	339.04 DEG	8975.10 FT	4981.72 FT	-1857.37 FT
11260.00 FT	47.48 DEG	339.65 DEG	9040.20 FT	5047.74 FT	-1882.26 FT
11353.00 FT	47.92 DEG	340.27 DEG	9102.79 FT	5112.36 FT	-1905.83 FT
11449.00 FT	48.19 DEG	340.00 DEG	9166.96 FT	5179.52 FT	-1930.09 FT
11545.00 FT	46.52 DEG	340.00 DEG	9231.99 FT	5245.67 FT	-1954.24 FT
11640.00 FT	46.69 DEG	340.18 DEG	9297.26 FT	5310.77 FT	-1977.75 FT
11736.00 FT	46.78 DEG	340.79 DEG	9363.06 FT	5376.67 FT	-2001.10 FT
11784.00 FT	46.87 DEG	340.97 DEG	9425.90 FT	5409.74 FT	-2012.57 FT

11784.00 FT	46.87 DEG	340.97 DEG	9395.90 FT	5409.74 FT	-2012.57 FT
11856.00 FT	46.87 DEG	340.97 DEG	9445.12 FT	5459.41 FT	-2029.70 FT

COMPANY Coastal Oil & Gas Corp.

WELL: OCS-G 19841 #1 ST1


FIELD: West Delta 112

COUNTY: Offshore

STATE: Louisiana

**TRUE VERTICAL DEPTH**

BOTTOM LOG INTERVAL	10886 ft
SCHLUMBERGER DEPTH	10937 ft
DEPTH DRILLER	11856 ft
KELLY BUSHING	111 ft
DRILL FLOOR	111 ft
GROUND LEVEL	-277 ft



Array Induction  
 Density - Neutron  
 True Vertical Depth  
 Final Composite [5"=100']