

DEPTH	DRIFT ANGLE	TRUE BEARING	HORIZONTAL DISTANCE	VERTICAL DEPTH	DEPARTURE (EAST +) (WEST -)	LATITUDE (NORTH +) (SOUTH -)	COORDINATES	
							X (EAST +) (WEST -)	Y (NORTH +) (SOUTH -)

3300	1.9	33	1.49	3299.98	.81	1.25	.81	1.25
3400	2.9	26	5.06	3399.85	2.22	4.55	3.03	5.80
3500	3.1	65	5.41	3499.70	4.90	2.29	7.93	8.08
3600	4.2	83	7.32	3599.43	7.27	.89	15.20	8.98
3700	6.6	87	11.49	3698.77	11.48	.60	26.68	9.58
3800	7.3	95	12.71	3797.96	12.66	-1.11	39.34	8.47
3900	7.2	93	12.53	3897.17	12.52	-.66	51.85	7.81
4000	7.0	89	12.19	3996.43	12.19	.21	64.04	8.03
4100	6.8	93	11.84	4095.72	11.82	-.62	75.86	7.41
4200	6.6	98	11.49	4195.06	11.38	-1.60	87.24	5.81
4300	6.3	93	10.97	4294.46	10.96	-.57	98.20	5.23
4400	6.3	98	10.97	4393.85	10.87	-1.53	109.07	3.71
4500	6.1	92	10.63	4493.28	10.62	-.37	119.69	3.34
4600	5.9	93	10.28	4592.76	10.27	-.54	129.95	2.80
4700	6.0	97	10.45	4692.21	10.37	-1.27	140.33	1.52
4800	5.7	99	9.93	4791.71	9.81	-1.55	150.14	-.03
4900	5.4	96	9.41	4891.27	9.36	-.98	159.50	-1.01
5000	5.0	93	8.72	4990.89	8.70	-.46	168.20	-1.47
5100	5.0	89	8.72	5090.51	8.71	.15	176.92	-1.32
5200	4.8	87	8.37	5190.16	8.36	.44	185.27	-.88
5300	4.7	86	8.19	5289.82	8.17	.57	193.45	-.31
5400	4.3	82	7.50	5389.54	7.42	1.04	200.87	.74
5500	4.0	80	6.98	5489.30	6.87	1.21	207.74	1.95
5600	3.7	71	6.45	5589.09	6.10	2.10	213.84	4.05
5700	3.5	70	6.10	5688.90	5.74	2.09	219.58	6.14
5800	4.1	65	7.15	5788.65	6.48	3.02	226.06	9.16
5900	4.2	59	7.32	5888.38	6.28	3.77	232.34	12.93
6000	3.5	40	6.10	5988.19	3.92	4.68	236.26	17.61
6100	4.3	32	7.50	6087.91	3.97	6.36	240.23	23.96
6200	4.6	23	8.02	6187.59	3.13	7.38	243.37	31.35
6300	5.2	12	10.80	6287.00	2.25	10.56	245.61	41.91
6400	7.5	7	13.06	6386.15	1.59	12.96	247.20	54.87



ds0057460

6500	7.2	4	12.54	6485.36	.87	12.50	248.08	67.37
6600	6.8	359	11.84	6584.65	-.21	11.84	247.87	79.21
6700	6.8	2	11.32	6684.01	.40	11.31	248.27	90.52
6800	5.7	359	9.93	6783.52	-.17	9.93	248.09	100.45
6900	5.6	356	9.76	6883.04	-.68	9.73	247.41	110.19
7000	5.6	356	9.76	6982.56	-.34	9.75	247.07	119.94
7100	5.5	358	9.58	7082.10	-.33	9.58	246.74	129.52
7200	5.1	366	8.89	7181.71	-.62	8.87	246.12	138.38
7300	4.6	350	8.02	7281.38	-1.39	7.90	244.73	146.28
7400	4.6	355	8.02	7381.06	-.70	7.99	244.03	154.27
7500	5.6	344	8.72	7480.68	-2.40	8.38	241.62	162.65
7600	5.6	350	9.24	7580.25	-1.60	9.10	240.02	171.75
7615	5.5	350	1.44	7595.18	-.25	1.42	239.77	173.16

8100

Projected (5-20-72)

WC 544 #1

STOOBPO1

5-14-72

from log

API # 17762.40056 (00)