

DEPTH	DRIFT ANGLE	TRUE BEARING	HORIZONTAL DISTANCE	VERTICAL DEPTH	DEPARTURE (EAST +) (WEST -)	LATITUDE (NORTH +) (SOUTH -)	COORDINATES	
							X (EAST +) (WEST -)	Y (NORTH +) (SOUTH -)
3300	.7	116	.54	3300.00	.48	-.24	.48	-.24
3400	1.0	235	1.75	3399.98	-1.43	-1.00	-.95	-1.24
3500	1.4	243	2.44	3499.95	-2.18	-1.11	-3.12	-2.35
3600	1.4	240	2.44	3599.92	-2.12	-1.22	-5.24	-3.57
3700	1.4	241	2.44	3699.89	-2.14	-1.18	-7.38	-4.75
3800	1.0	255	1.75	3799.88	-1.69	-.45	-9.06	-5.20
3900	1.3	330	2.27	3899.85	-1.13	1.96	-10.20	-3.24
4000	1.5	333	2.62	3999.82	-1.19	2.33	-11.38	-.91
4100	1.6	337	2.79	4099.78	-1.09	2.57	-12.48	1.66
4200	.6	65	1.06	4199.77	.95	.44	-11.53	2.11
4300	1.0	42	1.75	4299.76	1.17	1.30	-10.36	3.40
4400	1.2	33	2.09	4399.74	1.14	1.76	-9.22	5.16
4500	.5	80	.87	4499.73	.86	.15	-8.36	5.31
4600	.4	317	.70	4599.73	-.48	.51	-8.83	5.82
4700	.4	280	.70	4699.73	-.69	.12	-9.52	5.94
4800	1.6	267	2.79	4799.60	-2.79	-.15	-12.31	5.80
4900	1.9	268	3.32	4899.63	-3.31	-.12	-15.62	5.68
5000	2.0	280	3.49	4999.87	-3.44	.61	-19.06	6.29
5100	2.2	283	3.84	5099.50	-3.74	.86	-22.80	7.15
5200	2.1	286	3.66	5199.43	-3.52	1.01	-26.32	8.16
5300	2.5	307	4.36	5299.34	-3.48	2.63	-29.81	10.79
5400	2.4	326	4.19	5399.25	-2.34	3.47	-32.15	14.26
5500	2.4	330	4.19	5499.16	-2.09	3.63	-34.24	17.88
5600	2.6	318	4.54	5599.06	-3.04	3.37	-37.28	21.26
5700	2.6	306	4.54	5698.95	-3.67	2.67	-40.95	23.92
5800	2.9	300	5.06	5798.83	-4.38	2.53	-45.33	26.45
5900	3.0	280	5.23	5898.69	-5.15	.91	-50.48	27.36
6000	4.0	268	6.98	5998.45	-6.97	-.24	-57.46	27.12
6100	3.8	260	6.63	6098.23	-6.53	-1.15	-63.98	25.97
6200	3.6	260	6.28	6198.03	-6.18	-1.09	-70.17	24.88
6300	3.3	269	5.76	6297.86	-5.76	-.10	-75.92	24.77
6400	3.4	284	5.93	6397.69	-5.75	1.43	-81.68	26.21



ds0057461

6500	3.5	290	6.10	6497.50	-5.74	2.09	-87.41	28.30
6600	4.0	300	6.98	6597.26	-6.04	3.49	-93.45	31.79
6700	4.0	295	6.98	6697.01	-6.32	2.95	-99.78	34.73
6800	4.1	308	7.15	6796.76	-5.63	4.40	-105.41	30.14
6900	4.7	302	8.19	6896.42	-6.95	4.34	-112.36	43.48
7000	4.4	310	7.67	6996.13	-5.88	4.93	-118.24	48.41
7100	4.6	310	8.02	7095.80	-6.14	5.16	-124.38	53.66
7200	4.6	308	8.02	7195.48	-6.57	4.60	-130.95	58.16
7300	5.0	320	8.72	7295.10	-5.60	6.68	-136.95	64.84
7400	5.2	326	9.06	7394.69	-5.07	7.51	-141.62	72.35
7500	5.2	327	9.06	7494.28	-4.94	7.60	-146.56	79.96
7545	4.2	324	3.30	7539.16	-1.94	2.67	-148.49	82.62

TD 7809'
WC 544 #1

STOOBPOO

4-30-72 from log

API #17702. 40056 (70)