

2-7/8", 6.5 #/ft, N-80, ID=2.441", CS HYDRIL TBG to 12,409'
 2-3/8", 4.7#/ft, N-80, ID=1.995", CS HYDRIL TBG from 12,409' to 14,548'

KB to TH = 43'
 KB to MSL = 95'
 WD = 123'

12.2# CICIs Mud in Annulus

26" DP @ 461'

DXX Plug in Otis "X" L/N (ID=2.313") w/
 FC @ 3042'

Otis "X" L/N (ID=2.313") w/ FC @ 3117'

10-3/4" 40.5 / 45.5 #/ft., K-55 @ 4073'
Cmt'd with 3420 cubic ft. TOC at 4'

NOTE: Max hole angle 25 degrees @ 4400'
 Straight hole below 9700'

Top of Fish @ 12,339 WLM
 "W.L. Tool String w/ GS
 Pulling Tool & DX Plug"
 Crossover @ 12,409'

Top of 5" Liner @ 12,492'

7" 32 / 29 / 26 #/ft., N-80 @ 12,998'
Cmt'd with 3240 cubic ft. Calculated TOC at 753'

Otis "X" L/N (ID=1.875") @ 14,348'
 Baker "DB" Pkr @ 14,382'
 Otis "XO" Sliding Sleeve (ID=1.875") @ 14,461'
 2 Blast Joints @ 14,464' - 14,503'

Otis "XN" No Go Nipple (ID=1.79") @ 14,533'
 Baker "D" Pkr @ 14,534' IES
 Tubed to 14,548'

Baker "K" Retainer @ 14,569' IES

PBTD @
 14,569' MD
 14,066' TVD

5" Liner 8 RD 18# P110 @ 14,700'
Cmt'd with 310 cubic ft. TOC at 12492'

TD @ 14,700' MD / 14,196' TVD

S01

13200' D
Upper Lobe Perfs
 14,472' - 14,496'
 w/ 4 spf (original)
 14,470' - 14,525'
 w/ 8 spf (added in 1990)

S01

13200' D
Lower Lobe Perfs
 14,550' - 14,562' IES
 w/ 4 spf

VERMILION 214

VR214 OCS-G-2076 # B-3

API #17-705-40199-00-S01

Chevron U.S.A. Inc.

CURRENT COMPLETION

PBC/JPU

VR214#B3C

4/1/08

Critical Well Info

Spud Date: 6/30/76
 Completion Date: 12/28/76
 Chevno: AE7343